



Torch light suprabeam®

Suprabeam Q1r



Item no. 861241

Technical Data

Material housing: High strength aluminum, anodised
 Dimensions (L×Ø): 141.5 mm×15 mm
 Weight: 48 g
 Protection category: IP20
 Operating range of temperature: -20° C to +50° C
 Power source: 1×Li-Po 720 mAh
 Bright wide: 100 m
 Light power levels:
 - max: 550 lm
 - dimming: 125 lm-6 lm
 Luminous period:
 - max: 1 h
 - low dimming: 50 h

Suprabeam M6xr



Item no. 860804

Technical Data

Material housing: High strength aluminum, anodised
 Dimensions (L×Ø): 110 mm×tube 23 mm, head 32 mm
 Weight: 114 g
 Protection category: IP68
 Operating range of temperature: -20° C to +50° C
 Power source: Li-Ion 3·000 mAh
 Bright wide: Mixed beam 30°/70°/165 m
 Light power levels:
 - max: 2'000 lm
 - dimming: 600 lm-6 lm
 Luminous period:
 - max: 2 h 15 min
 - dimming: 2 h 30 min-260 h

Suprabeam Q3r



Item no. 861242

Technical Data

Material housing: High strength aluminum, anodised
 Dimensions (L×Ø): 122 mm×26.5 mm
 Weight mit Akku: 130 g
 Protection category: IP68
 Operating range of temperature: -20° C to +50° C
 Power source: Li-Ion 3'000 mAh
 Bright wide: 200 m
 Light power levels:
 - max: 1'100 lm
 - dimming: 600 lm-6 lm
 Luminous period:
 - max: 1 h 45 min
 - low dimming: 300 h

Suprabeam Q3classic



Item no. 860703

Technical Data

Material housing: High strength aluminum, anodised
 Dimensions (L×Ø): 115.3 mm×26.5 mm
 Weight: 96 g
 Protection category: IPX8
 Operating range of temperature: -20° C to +50° C
 Power source: 3×AAA
 Bright wide: 210 m
 Light power levels: 330 lm
 Luminous period: 20 h

| Item no. | Designation |
|----------|---|
| ✓ 861241 | Torch light LED Suprabeam Q1r 550 lm, incl. 1×Li-Po accu, USB-C cable |
| ✓ 861242 | Torch light LED Suprabeam Q3r 1'100 lm, incl. 1×Li-Ion accu, USB-C cable |

| Accessories/spare parts | |
|-------------------------|--|
| ✓ 250023 | Spare battery Li-Ion for Suprabeam Q3r |
| ✓ 861244 | Signal cone orange for Q3r |

| Item no. | Designation |
|----------|--|
| ✓ 860804 | Multifunction lamp LED Suprabeam M6xr, 2'000 lm, incl. 1×Li-Ion accu, USB-C adapter, headband, quick-release fastener, integrated magnetic base |
| ✓ 860703 | Torch light LED Suprabeam Q3classic, 330 lm, incl. 3×AAA batteries and belt pouch |

| Accessories/spare parts | |
|-------------------------|---|
| ✓ 860805 | Spare battery Li-Ion for Suprabeam M6xr |
| ✓ 861243 | Charger 4-fold (set with 4 batteries) for Suprabeam M6xr |
| ✓ 021811 | Battery LR03 AAA/1.5 V (apiece) |

✓ from stock, offer subject to prior sale

Torch light suprabeam®

Suprabeam Q5xrs defend



Item no. 861099



Technical Data

| | |
|---------------------------------|----------------------------------|
| Material housing: | High strength aluminum, anodised |
| Dimensions (L×Ø): | 161 mm×39 mm |
| Weight: | 182 g |
| Protection category: | IPX4 |
| Operating range of temperature: | -20° C to +35° C |
| Power source: | Li-Ion 3'300mAh |
| Light power levels: | |
| – max: | 2'000 lm |
| – medium: | 400 lm |
| – low: | 50 lm |
| – strobe: | 10 Hz |
| Luminous period: | |
| – max: | 1 h 15 min |
| – medium: | 3 h 30 min |
| – low: | 28 h |

| Item no. | Designation |
|----------|--|
| ✓ 861099 | Torch light LED Suprabeam, Q5xrs, defend 2'000lm, incl. 1×Li-Ion accu, USB-C cable |

| Accessories/spare parts | |
|-------------------------|--|
| ✓ 861044 | Spare battery Li-Ion 3'300mAh for Suprabeam Q5xrs defend |
| ✓ 860708 | Signal cone orange for Q5xrs defend |

Headlamp suprabeam®

Suprabeam S4 rechargeable



Item no. 860947

Technical Data

| | |
|-------------------------------------|------------------------|
| Material housing: | Hi-Tech plastic |
| Headband: | Adjustable to 50-70 cm |
| Weight incl. battery: | 136 g |
| Protection category: | IP68 |
| Operating range of temperature: | -20° C to +35° C |
| Power source: | Li-Po 1'400 mAh |
| Bright wide: | 100 m |
| Light power levels/luminous period: | |
| – max: | 750 lm/5 h 30 min |
| – medium: | 250 lm/8 h |
| – low: | 75 lm/18 h |

Suprabeam V3pro rechargeable



Item no. 860707

Technical Data

| | |
|-------------------------------------|---|
| Material housing: | Hi-Tech plastic composite with high strength aluminum |
| Headband: | Adjustable to 50-70 cm |
| Weight incl. battery: | 184 g |
| Protection category: | IPX4 |
| Operating range of temperature: | -20° C to +50° C |
| Power source: | Li-Po 2'800 mAh |
| Bright wide: | 245 m |
| Light power levels/luminous period: | |
| – max: | 1'000 lm/3 h |
| – medium: | 180 lm/8 h |
| – dimmung: | 6 lm-300 lm/max. 225 h |

| Item no. | Designation |
|----------|---|
| ✓ 860947 | Headlamp LED Suprabeam V3pro rechargeable 1'000 lm, incl. 1×Li-Po accu, USB cable |
| ✓ 860707 | Headlamp LED Suprabeam S4 rechargeable 750 lm, incl. 1×Li-Po accu, USB cable |

| Accessories/spare parts | |
|-------------------------|--|
| ✓ 216788 | Spare battery Li-Po for Suprabeam S4 rechargeable |
| ✓ 860709 | Spare accumulator Li-Po for Suprabeam V3pro rechargeable |
| ✓ 216790 | Helmet Clip for Suprabeam S4 rechargeable |
| ✓ 217308 | Helmet Clip-Set for Suprabeam S4 rechargeable |
| ✓ 227473 | Silicone headband black for Suprabeam V3pro rechargeable |



✓ from stock, offer subject to prior sale

2/2